

Listing of Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A composite vapor barrier for use between one or more spaces defined by the structural elements of a building, said composite vapor barrier comprising:

a first facing layer formed from a material that is generally impermeable to water vapor, wherein at least one surface of said first facing layer is applied with an adhesive coating; and

a scrim thermally bonded to said first facing layer;

wherein the composite vapor barrier does not substantially rupture when a bag of sand having a weight of approximately 400 pounds and a diameter of approximately 30 inches is dropped onto said composite vapor barrier from a distance of about 42 inches above an upper surface of said composite vapor barrier.

2. (Original) A composite vapor barrier as defined in claim 1, wherein said first facing layer is formed from a material selected from the group consisting of vinyl, a metallized film, foil, a polyolefin, kraft, and combinations thereof.

3. (Original) A composite vapor barrier as defined in claim 1, wherein said first facing layer is formed from a metallized film.

4. (Original) A composite vapor barrier as defined in claim 1, further comprising a second layer formed from a material that is generally impermeable to water vapor.

5. (Original) A composite vapor barrier as defined in claim 4, wherein said first and said second facing layers are formed from a material selected from the group consisting of vinyl, a metallized film, foil, a polyolefin, kraft, and combinations thereof.

6. (Original) A composite vapor barrier as defined in claim 4, wherein said second facing layer is formed from vinyl.

7. (Original) A composite vapor barrier as defined in claim 4, wherein said first facing layer is formed from a metallized film and said second layer is formed from vinyl.

8. (Original) A composite vapor barrier as defined in claim 1, wherein said scrim is a triaxial scrim.

9. (Original) A composite vapor barrier as defined in claim 1, wherein said scrim includes threads formed from polyester fibers.

10. (Original) A composite vapor barrier as defined in claim 1, wherein said scrim has a weight at least about 2 ounces per square yard.

11. (Original) A composite vapor barrier as defined in claim 1, wherein said scrim has a weight of between about 2 ounces per square yard to about 8 ounces per square yard.

12. (Original) A composite vapor barrier as defined in claim 1, wherein said scrim has a weight of between about 3.0 ounces per square yard to about 6.5 ounces per square yard.

13. (Original) A composite vapor barrier as defined in claim 1, wherein said vapor barrier has a weight of between about 3 ounces per square yard to about 10 ounces per square yard.

14. (Original) A composite vapor barrier as defined in claim 1, wherein said vapor barrier has a weight of between about 6 ounces per square yard to about 9 ounces per square yard.

15. (Original) A composite vapor barrier as defined in claim 1, wherein said vapor barrier has an average thickness of less than about 0.03 inches.

16. (Original) A composite vapor barrier as defined in claim 1, wherein said scrim includes a selvage area that contains an additional number of machine-direction threads.

17. (Cancelled)

18. (Original) A composite vapor barrier for use between one or more spaces defined by the structural elements of a building, said composite vapor barrier comprising:

a first facing layer comprising a metallized film that is generally impermeable to water vapor;

a second facing layer comprising a vinyl material that is generally impermeable to water vapor, wherein at least one surface of at least one of said facing layers is applied with an adhesive coating; and

a triaxial scrim thermally bonded to and positioned between said first and said second facing layers;

wherein the composite vapor barrier does not substantially rupture when a bag of sand having a weight of approximately 400 pounds and a diameter of approximately 30 inches is dropped onto said composite vapor barrier from a distance of about 42 inches above an upper surface of said composite vapor barrier.

19. (Original) A composite vapor barrier as defined in claim 18, wherein said scrim includes machine-direction and cross-direction threads.

20. (Original) A composite barrier as defined in claim 19, wherein machine-direction and said cross-direction threads are formed from polyester fibers.

21. (Original) A composite vapor barrier as defined in claim 19, wherein said scrim includes a selvage area that contains an additional number of machine-direction threads.

22. (Original) A composite vapor barrier as defined in claim 18, wherein said scrim has a weight of between about 3.0 ounces per square yard to about 6.5 ounces per square yard.

23. (Original) A composite vapor barrier as defined in claim 18, wherein said vapor barrier has a weight of between about 6 ounces per square yard to about 9 ounces per square yard.

24-32. (Withdrawn)

33. (New) A composite vapor barrier as defined in claim 1, wherein the scrim includes threads containing fiberglass.

34. (New) A composite vapor barrier as defined in claim 18, wherein the scrim includes threads containing fiberglass.